



IPC
BY TENNANT COMPANY

SCRUBBERDRYERS - WALK BEHIND

CT51



MAX PRODUCTIVITY

Up to
3150m²/h

**BATTERIES
RUNNING TIME**

3,5 h

**WATER TANK
RUNNING TIME**

60'
working session

TELEMATICS GPS (optional)
GEOLOCATION OF ALL YOUR MACHINES

MEMORY CARD

ANC
ADVANCE NOISE CONTROL
INECO SELECT MODE
54dB



ORBITAL VERSION



ONE BRUSH VERSION



ROLLER VERSION



CERTIFICATIONS

GREEN CLEANING EFFICIENCY

ISO 14067 CARBON FOOTPRINT CERTIFIED

BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE

RETAIL

HORECA

CLEANING CONTRACTORS

MUNICIPALITIES

INNOVATIONS

INTER-CHANGEABLE BRUSH HEAD

600 RPM IN T ERCH A NGE A B LE BRUSH HEAD

ORBITAL BRUSH

DBL DOUBLE BATTERY LIFE

MEMORY CARD

SLS SELF LEVELING SYSTEM


ECO SELECT

SERVICE MENU

HEPA FILTER

ANTIBACTERIAL PLASTIC


SPECS



ADJUSTABLE HANDLE FOR A COMFORTABLE AND EASY USE



FULL MACHINE CONTROL THANKS TO AN INTUITIVE CENTRAL KNOB



EASY ACCESS NO TOOLS

TECHNICAL DATA

WITHOUT ELECTRIC TRACTION

WITH ELECTRIC TRACTION

		CT51 B50	CT51 B55	CT51 BT55	CT51 BT55 ANTIBACTERIAL	CT51 BT70
Code		LPTB02976	LPTB01822	LPTB01823	LPTB03425	LPTB01824
PERFORMANCE						
Max theoretical productivity	m ² /h	1850	1925	2475	2475	3150
Cleaning path	mm	500	550	550	550	700
Water tank capacity (solution recovery)	l	50/53	50/53	50/53	50/53	50/53
Max running time	min	210	210	210	210	210
Voltage	V-Ah	24	24	24	24	24
Installed power	W	800	800	1000	1000	1400
Brush pressure	kg	18	18	18	18	23
Squeegee width	mm	815	815	815	815	940
Max speed	km/h	3,5	3,5	4,5	4,5	4,5
Weight (Without Batteries)	kg	81,1	81,4	89,1	89,1	94,6
Dimension (LxWxH)	mm	1328 x 563 x 1033	1328 x 563 x 1033	1329 x 563 x 1033	1329 x 563 x 1033	1279 x 735 x 1033

STANDARD EQUIPMENT

		CT51 B50	CT51 B55	CT51 BT55	CT51 BT55 ANTIBACTERIAL	CT51 BT70
BRUSHES PPL SOFT						
SQUEEGEE BLADES						
LATEX FRONT BLADE		SPPV01332	SPPV01352	SPPV01352	SPPV01352	2xSPPV01472
LATEX REAR BLADE		MPVR08039 - 880mm MPVR08035 - 900mm	MPVR08040 - 1020mm MPVR08036 - 1020mm			

CABLE

		CT51 C50 230V LPTE00669	CT51 C55 230V LPTE00646
PERFORMANCE			
Max theoretical productivity	m ² /h	1850	1925
Cleaning path	mm	500	550
Water tank capacity (solution recovery)	l	50/53	50/53
Max running time	min	Unlimitess	Unlimitess
Voltage	V-Ah	230	230
Installed power	W	1100	1100
Brush pressure	kg	18	18
Squeegee width	mm	815	815
Max speed	km/h	3,5	3,5
Weight (Without Batteries)	kg	102	102,1
Dimension (LxWxH)	mm	1329 x 563 x 1033	1329 x 563 x 1033

STANDARD EQUIPMENT

		CT51 C50 230V	CT51 C55 230V
BRUSHES			
PPL SOFT			
		SPPV01332	SPPV01352
SQUEEGEE BLADES			
LATEX FRONT BLADE		MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE		MPVR08035 - 900mm	MPVR08035 - 900mm

TECHNICAL DATA

WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

ROLLER - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

		CT51 XP70 LPTB01825	CT51 XP55R LPTB01834
Code			
PERFORMANCE			
Max theoretical productivity	m ² /h	3150	2475
Cleaning path	mm	700	550
Water tank capacity (solution recovery)	l	50/53	50/53
Max running time	min	210	210
Voltage	V-Ah	24	24
Installed power	W	1450	2350
Brush pressure	kg	31	18
Squeegee width	mm	940	815
Max speed	km/h	4,5	4,5
Weight (Without Batteries)	kg	94,6	107
Dimension (LxWxH)	mm	1279 x 735 x 1033	1329 x 563 x 1033

STANDARD EQUIPMENT

	CT51 XP70	CT51 XP55R
BRUSHES		
PPL SOFT	2XSPPV01472	-
CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm	-	SPPV01163
SQUEEGEE BLADES		
LATEX FRONT BLADE	MPVR08040 - 1020mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08036 - 1020mm	MPVR06288 - 715mm

600 RPM - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

ORBITAL - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

	CT51 XP55 600 RPM LPTB01832	CT51 XP70 600 RPM LPTB01833	CT51 XP20" ORBITAL LPTB01670
Code			
PERFORMANCE			
Max theoretical productivity	m ² /h	3150	2794
Cleaning path	mm	700	500
Water tank capacity (solution recovery)	l	50/53	50/53
Max running time	min	210	210
Voltage	V-Ah	24	24
Installed power	W	1080	1080
Brush pressure	kg	26	45,7
Motor	rpm	600	2200
Brush	mm	815	815
RPM	km/h	4,5	4,2
Squeegee width	kg	89,1	107,2
Max speed	mm	1329 x 563 x 1033	1225 x 512 x 1033
Weight (Without Batteries)			
Dimension (LxWxH)			

STANDARD EQUIPMENT

	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP20" ORBITAL
PAD HOLDER			
MICROFIBER PAD HOLDER	SPPV0197	2x	-
DIAMOND PAD HOLDER	8	SPPV01983	-
SQUEEGEE BLADES			
LATEX FRONT BLADE	SPPV0134	2x	
LATEX REAR BLADE	MPVR08039 - 880mm	MPVR08040 - 1020mm	MPVR08039 - 880mm
	MPVR08035 - 900mm	MPVR08036 - 1020mm	MPVR08035 - 900mm

CONSUMABLES (Codes available on price list)

	CONSUMABLES	CODE	CT51 C50	CT51 C55	CT51 B50	CT51 B55	CT51 BT55	CT51 BT70	CT51 XP70	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP55 R	CT51XP50 ORBITAL
	Brushes	available on price list	•	•	•	•	•	•	•	•	•		
	Roller Brushes	available on price list										•	
	Pad holder	available on price list	•	•	•	•	•	•	•	•	•		
	Pads	available on price list	•	•	•	•	•	•	•	•	•		
	Orbital pads	available on price list											•
	Microfiber pads	available on price list								•	•		
	Diamond pads	available on price list								•	•		
	Squeegee blades	available on price list	•	•	•	•	•	•	•	•	•	•	•

OPTIONAL ACCESSORIES

	BRUSH HEAD	CODE	CT51 C50	CT51 C55	CT51 B50	CT51 B55	CT51 BT55	CT51 BT70	CT51 XP70	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP55 R	CT51XP20" ORBITAL
	C50 C55 B5 0 B5 5		NOT INTERCHANGEABLE BRUSH HEAD										
	BT55	KTRI04851							•	•	•	•	•
	BT60	KTRI04852							•	•	•	•	•
	BT70	KTRI04853							•	•	•	•	•
	XP55 600 RPM	KTRI04855								•	•	•	•
	XP70 600 RPM	KTRI04856								•	•	•	•
	XP55 ROLLER	KTRI04854								•	•	•	•
	XP20" ORBITAL	KTRI05787								•	•	•	•
	Kit Telematic Basic	KTRI06165			•	•							
		KTRI06163					•	•	•	•	•	•	•
	Kit Telematic Full	KTRI06164			•	•							
		KTRI06024					•	•	•	•	•	•	•

OPTIONAL ACCESSORIES

	OPTIONAL	CODE	CT51 C50	CT51 C55	CT51 B50	CT51 B55	CT51 BT55	CT51 BT70	CT51 XP70	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP55 R	CT51XP50 ORBITAL
 	HEPA Filter	KTRI06666	•	•	•	•	•	•	•	•	•	•	•
	Chem dose kit	KTRI04846			•	•	•	•	•	•	•	•	•
	Splash guard 50/55 cm	KTRI05244		•	•	•	•			•			
	Splash guard 60 cm	KTRI05245											
	Splash guard 70 cm	KTRI05246						•	•		•		
	Tools bar	KTRI04848	•	•	•	•	•	•	•	•	•	•	•
	Auto-Refill System	KTRI04849	•	•	•	•	•	•	•	•	•	•	•
	External suction kit	KTRI02257	•	•	•	•	•	•	•	•	•	•	•

BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah (C5)	345x170x28	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah (C5)	345x174x283	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133
EXIDE gel battery BAAC00132	2	12V 76 Ah (C5)	330x171x236	150 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah (C5)	308x175x225	150 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060
Dry charge flate plate BAAC00009	2	12V 105 Ah (C5)	261x171x210	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060
Acid tubular plate BAAC00070	2	12V 118 Ah (C5)	345x170x285	210 min	DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060

RECOMMENDED BATTERIES AND BATTERY CHARGER

WH-B05, Block B, UAQ Free Trade Zone, Ahmed Bin Rashid Port, Umm Al Quwain, UAE
Tel. +971525453816| info@aura-max.com - www.aura-max.com