



IPC

BY TENNANT COMPANY



PLANET 300S PN ATEX
EXCLUSIVE FEATURES



PNEUMATIC/
AIR OPERATED



CE EX II 3D Ex t IIIB T135°C Dc IP55

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ TANGENTIAL OR METAL INLET
- ▶ FILTER OVERPRESSURE INDICATORS
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ STATIC DISSIPATING FILTERS
- ▶ PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ GROUNDING SYSTEM

PLANET 300 S PN ATEX
ASID00293

Code		PLANET 300 S PN ATEX
TECHNICAL DATA		ASID00293
Usage		DRY
Air consumption	l/min	700-1300
Air pressure	bar	6
Water lift	mmH2O	2200-3300
Air flow	m3/h	330
Tank capacity	l	100
Diameter of inlet	mm	70
Dimensions (LxWxH)	mm	630 x 890 x 1650
Weight	kg	72

STANDARD EQUIPMENT

CODE: KTRI04594
CONDUCTIVE
FILTERING KIT



CODE: FTDP40014
POLYCARBON PREFILTER



CODE: FTDP00375
POLYESTER CARTRIDGE
10.000 cm²



OPTIONAL ACCESSORIES

Anti-static kit tools for inlet Ø50-70 mm	PMDT00426
Stainless steel float kit to recovery liquid (for Planet 100 lt)	KTRI03124
Reusable conductive bag Atex (for Planet 100 lt)	KTRI03175
Retainer plate with clip (for conductive bag)	PVVR00190

RECOMMENDED BATTERIES AND BATTERY CHARGER

WH-B05, Block B, UAQ Free Trade Zone, Ahmed Bin Rashid Port, Umm Al Quwain, UAE
Tel. +971525453816 | info@aura-max.com - www.aura-max.com