



SCRUBBERDRYERS-WALK BEHIND

CT51



MAX PRODUCTIVITY

Up to
3150^{m2/h}

**BATTERIES
RUNNING TIME**

3,5 h

**WATER TANK
RUNNING TIME**

60'

Upto
working session

TELEMATICS GPS (optional)

GEOLOCATION OF
ALL YOUR MACHINES



ORBITAL VERSION



ONE BRUSH VERSION



ROLLER VERSION



CERTIFICATIONS



BATTERIES AND BATTERY CHARGER NOT INCLUDED


MOST FREQUENTLY USE



INNOVATIONS




SPECS



ADJUSTABLE HANDLE FOR
A COMFORTABLE AND EASY
USE



FULL MACHINE CONTROL
THANKS TO AN
INTUITIVE CENTRAL
KNOB



EASY ACCESS NO TOOLS

RECOMMENDED BATTERIES AND BATTERY CHARGER

WH-B05, Block B, UAQ Free Trade Zone, Ahmed Bin Rashid Port, Umm Al Quwain, UAE
Tel. +971525453816 | info@aura-max.com - www.aura-max.com

TECHNICAL DATA

WITHOUT ELECTRIC TRACTION

WITH ELECTRIC TRACTION

| | | CT51 B50 | CT51 B55 | CT51 BT55 | CT51 BT55 ANTIBACTERIAL | CT51 BT70 |
|-----------------------------------------|-------------------|-------------------|-------------------|-------------------|----------------------------|-------------------|
| Code | | LPTB02976 | LPTB01822 | LPTB01823 | LPTB03425 | LPTB01824 |
| PERFORMANCE | | | | | | |
| Max theoretical productivity | m ² /h | 1850 | 1925 | 2475 | 2475 | 3150 |
| Cleaning path | mm | 500 | 550 | 550 | 550 | 700 |
| Water tank capacity (solution recovery) | l | 50/53 | 50/53 | 50/53 | 50/53 | 50/53 |
| Max running time | min | 210 | 210 | 210 | 210 | 210 |
| Voltage | V-Ah | 24 | 24 | 24 | 24 | 24 |
| Installed power | W | 800 | 800 | 1000 | 1000 | 1400 |
| Brush pressure | kg | 18 | 18 | 18 | 18 | 23 |
| Squeegee width | mm | 815 | 815 | 815 | 815 | 940 |
| Max speed | km/h | 3,5 | 3,5 | 4,5 | 4,5 | 4,5 |
| Weight (Without Batteries) | kg | 81,1 | 81,4 | 89,1 | 89,1 | 94,6 |
| Dimension (LxWxH) | mm | 1328 x 563 x 1033 | 1328 x 563 x 1033 | 1329 x 563 x 1033 | 1329 x 563 x 1033 | 1279 x 735 x 1033 |

STANDARD EQUIPMENT

| | | CT51 B50 | CT51 B55 | CT51 BT55 | CT51 BT55 ANTIBACTERIAL | CT51 BT70 |
|-------------------------|--|----------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|------------------------------------------|
| BRUSHES PPL SOFT | | | | | | |
| SQUEEGEE BLADES | | | | | | |
| LATEX FRONT BLADE | | SPPV01332 | SPPV01352 | SPPV01352 | SPPV01352 | 2xSPPV01472 |
| LATEX REAR BLADE | | MPVR08039 - 880mm MPVR08035 - 900mm | MPVR08040 - 1020mm MPVR08036 - 1020mm |

CABLE

| | | CT51 C50 230V LPTE00669 | CT51 C55 230V LPTE00646 |
|-----------------------------------------|-------------------|----------------------------|----------------------------|
| PERFORMANCE | | | |
| Max theoretical productivity | m ² /h | 1850 | 1925 |
| Cleaning path | mm | 500 | 550 |
| Water tank capacity (solution recovery) | l | 50/53 | 50/53 |
| Max running time | min | Unlimitess | Unlimitess |
| Voltage | V-Ah | 230 | 230 |
| Installed power | W | 1100 | 1100 |
| Brush pressure | kg | 18 | 18 |
| Squeegee width | mm | 815 | 815 |
| Max speed | km/h | 3,5 | 3,5 |
| Weight (Without Batteries) | kg | 102 | 102,1 |
| Dimension (LxWxH) | mm | 1329 x 563 x 1033 | 1329 x 563 x 1033 |

STANDARD EQUIPMENT

| | | CT51 C50 230V | CT51 C55 230V |
|------------------------|--|-------------------|-------------------|
| BRUSHES | | | |
| PPL SOFT | | | |
| | | SPPV01332 | SPPV01352 |
| SQUEEGEE BLADES | | | |
| LATEX FRONT BLADE | | MPVR08039 - 880mm | MPVR08039 - 880mm |
| LATEX REAR BLADE | | MPVR08035 - 900mm | MPVR08035 - 900mm |

TECHNICAL DATA

WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

ROLLER - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

| | | CT51 XP70 | CT51 XP55R |
|-----------------------------------------|-------------------|-------------------|-------------------|
| Code | | LPTB01825 | LPTB01834 |
| PERFORMANCE | | | |
| Max theoretical productivity | m ² /h | 3150 | 2475 |
| Cleaning path | mm | 700 | 550 |
| Water tank capacity (solution recovery) | l | 50/53 | 50/53 |
| Max running time | min | 210 | 210 |
| Voltage | V-Ah | 24 | 24 |
| Installed power | W | 1450 | 2350 |
| Brush pressure | kg | 31 | 18 |
| Squeegee width | mm | 940 | 815 |
| Max speed | km/h | 4,5 | 4,5 |
| Weight (Without Batteries) | kg | 94,6 | 107 |
| Dimension (LxWxH) | mm | 1279 x 735 x 1033 | 1329 x 563 x 1033 |

STANDARD EQUIPMENT

| | CT51 XP70 | CT51 XP55R |
|---------------------------------------------|--------------------|-------------------|
| BRUSHES PPL SOFT CYLINDRICAL BRUSH - | | |
| PPL SOFT Ø 0,3 mm | 2XSPPV01472 | - |
| SQUEEGEE BLADES | | SPPV01163 |
| LATEX FRONT BLADE LATEX REAR BLADE | | |
| | MPVR08040 - 1020mm | MPVR08039 - 880mm |
| | MPVR08036 - 1020mm | MPVR06288 - 715mm |

600 RPM - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

ORBITAL - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

| | CT51 XP55 600 RPM LPTB01832 | CT51 XP70 600 RPM LPTB01833 | CT51 XP20" ORBITAL LPTB01670 |
|-----------------------------------------|--------------------------------|--------------------------------|---------------------------------|
| Code | | | |
| PERFORMANCE | | | |
| Max theoretical productivity | m ² /h | 3150 | 2794 |
| Cleaning path | mm | 700 | 500 |
| Water tank capacity (solution recovery) | l | 50/53 | 50/53 |
| Max running time | min | 210 | 210 |
| Voltage | V-Ah | 24 | 24 |
| Installed power | W | 1080 | 1080 |
| Brush pressure | kg | 26 | 45,7 |
| Motor RPM | rpm | 600 | 2200 |
| Brush RPM | rpm | 600 | 2200 |
| Squeegee width | mm | 815 | 815 |
| Max speed | km/h | 4,5 | 4,2 |
| Weight (Without Batteries) | kg | 89,1 | 107,2 |
| Dimension (LxWxH) | mm | 1329 x 563 x 1033 | 1225 x 512 x 1033 |

STANDARD EQUIPMENT

| | CT51 XP55 600 RPM | CT51 XP70 600 RPM | CT51 XP20" ORBITAL |
|------------------------|-------------------|--------------------|--------------------|
| PAD HOLDER | | | |
| MICROFIBER PAD HOLDER | SPPV0197 | 2x | - |
| DIAMOND PAD HOLDER | 8 | SPPV01983 | - |
| SQUEEGEE BLADES | | | |
| LATEX FRONT BLADE | SPPV0134 | 2x | |
| LATEX REAR BLADE | MPVR08039 - 880mm | MPVR08036 - 1020mm | MPVR08039 - 880mm |
| | MPVR08035 - 900mm | MPVR06288 - 715mm | MPVR08035 - 900mm |

CONSUMABLES (Codes available on price list)

| | CONSUMABLES | CODE | CT51 C50 | CT51 C55 | CT51 B50 | CT51 B55 | CT51 BT55 | CT51 BT70 | CT51 XP70 | CT51 XP55 600 RPM | CT51 XP70 600 RPM | CT51 XP55 R | CT51XP50 ORBITAL |
|-------------------------------------------------------------------------------------|-----------------|-------------------------|----------|----------|----------|----------|-----------|-----------|-----------|-------------------|-------------------|-------------|------------------|
|  | Brushes | available on price list | • | • | • | • | • | • | • | • | • | | |
|  | Roller Brushes | available on price list | | | | | | | | | | • | |
|  | Pad holder | available on price list | • | • | • | • | • | • | • | • | • | | |
|  | Pads | available on price list | • | • | • | • | • | • | • | • | • | | |
|  | Orbital pads | available on price list | | | | | | | | | | | • |
|  | Microfiber pads | available on price list | | | | | | | | • | • | | |
|  | Diamond pads | available on price list | | | | | | | | • | • | | |
|  | Squeegee blades | available on price list | • | • | • | • | • | • | • | • | • | • | • |

OPTIONAL ACCESSORIES

| | BRUSH HEAD | CODE | CT51 C50 | CT51 C55 | CT51 B50 | CT51 B55 | CT51 BT55 | CT51 BT70 | CT51 XP70 | CT51 XP55 600 RPM | CT51 XP70 600 RPM | CT51 XP55 R | CT51XP20" ORBITAL |
|-------------------------------------------------------------------------------------|------------------------------------|-----------|--------------------------------|----------|----------|----------|-----------|-----------|-----------|-------------------|-------------------|-------------|-------------------|
|  | C50 C55 B5 0 B5 5 BT55 | | NOT INTERCHANGEABLE BRUSH HEAD | | | | | | | | | | |
|  | | KTRI04851 | | | | | • | • | • | • | • | • | • |
|  | BT60 | KTRI04852 | | | | | • | • | • | • | • | • | • |
|  | BT70 | KTRI04853 | | | | | • | • | • | • | • | • | • |
|  | XP55 600 RPM | KTRI04855 | | | | | | | • | • | • | • | • |
|  | XP70 600 RPM | KTRI04856 | | | | | | | • | • | • | • | • |
|  | XP55 ROLLER | KTRI04854 | | | | | | | • | • | • | • | • |
|  | XP20" ORBITAL | KTRI05787 | | | | | | | • | • | • | • | • |
|  | Kit Telematic Basic | KTRI06165 | | | • | • | | | | | | | |
| | | KTRI06163 | | | | | • | • | • | • | • | • | • |
| | Kit Telematic Full | KTRI06164 | | | • | • | | | | | | | |
| | | KTRI06024 | | | | | • | • | • | • | • | • | • |

OPTIONAL ACCESSORIES

| | OPTIONAL | CODE | CT51 C50 | CT51 C55 | CT51 B50 | CT51 B55 | CT51 BT55 | CT51 BT70 | CT51 XP70 | CT51 XP55 600 RPM | CT51 XP70 600 RPM | CT51 XP55 R | CT51XP50 ORBITAL |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------|----------|----------|----------|----------|-----------|-----------|-----------|-------------------|-------------------|-------------|------------------|
|   | HEPA Filter | KTRI06666 | • | • | • | • | • | • | • | • | • | • | • |
|  | Chem dose kit | KTRI04846 | | | • | • | • | • | • | • | • | • | • |
|  | Splash guard 50/55 cm | KTRI05244 | | • | • | • | • | | | • | | | |
|  | Splash guard 60 cm | KTRI05245 | | | | | | | | | | | |
|  | Splash guard 70 cm | KTRI05246 | | | | | | • | • | | • | | |
|  | Tools bar | KTRI04848 | • | • | • | • | • | • | • | • | • | • | • |
|  | Auto-Refill System | KTRI04849 | • | • | • | • | • | • | • | • | • | • | • |
|  | External suction kit | KTRI02257 | • | • | • | • | • | • | • | • | • | • | • |

BATTERIES AND BATTERY CHARGERS

| BATTERIES | N° | CHARACTERISTICS | DIMENSION | RUNNING TIME | BATTERY CHARGERS |
|-------------------------------------|----|-----------------|-------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC gel battery BAAC00105 | 2 | 12V 105 Ah (C5) | 345x170x28 | 210 min | DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 - BACA00133 |
| EXIDE gel battery BAAC00024 | 2 | 12V 105 Ah (C5) | 345x174x28 | 210 min | DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 |
| EXIDE gel battery BAAC00132 | 2 | 12V 76 Ah (C5) | 330x171x23 | 150 min | DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 |
| Acid tubular plate BAAC00136 | 2 | 12V 85 Ah (C5) | 308x175x225 | 150 min | DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 |
| Dry charge flate plate BAAC00009 | 2 | 12V 105 Ah (C5) | 261x171x210 | 210 min | DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 |
| Acid tubular plate BAAC00070 | 2 | 12V 118 Ah (C5) | 345x170x285 | 210 min | DBL on board high freq. 24V 13 Ah- KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone low frequency 24V 12 Ah BACA0060 |

RECOMMENDED BATTERIES AND BATTERY CHARGER

WH-B05, Block B, UAQ Free Trade Zone, Ahmed Bin Rashid Port, Umm Al Quwain, UAE
Tel. +971525453816| info@aura-max.com - www.aura-max.com